



Nautic line - Mineral

Eurol Nautic L. 25W-40 FCW

4 stroke oil for outboard motors

Description

Eurol Nautic Line 25W-40 FCW is a motor oil that ensures an optimal lubrication and protection of 4 stroke outboard motors.

Eurol Nautic Line 25W-40 FCW fulfils the NMMA FCW requirements, such as protection against rust and corrosion through contact with (salt) water, a limited decrease in viscosity after long-term use and an excellent protection against wear and sedimentation, especially in case of fuel dilution*.

*Fuel dilution can happen in outboard motors, when the motor runs for an extended time in neutral, and unburnt fuel leaks into the crankcase. Eurol Nautic Line 25W-40 FCW contains special additives that limit wear to a minimum both at low and high speeds.

Thanks to special additives, Eurol Nautic Line 25W-40 FCW will keep providing its high performance level even after the oil change term has passed. However, it is always best to ensure timely oil changes.

Performance level

- API SL
- JASO MA
- NMMA FC-W

Physical properties

Colour	brown	
Density at 20°C	0.888 kg/l	ASTM D 4052
Viscosity, kinematic at 40°C	145.1 cSt	ASTM D 445
Viscosity, kinematic at 100°C	15.1 cSt	ASTM D 445
Viscosity Index	105	ASTM D 2270
Viscosity, dynamic (CCS)	6130 cP	ASTM D 5293
Sulphated ash	0.89 wt%	ASTM D 874
Flash point	211 °C	ASTM D 93
Pour point	-24 °C	ASTM D 97

Article number E100138
Version 1.0, 25-03-2016

Eurol B.V. Energiestraat 12, 7442 DA Nijverdal, The Netherlands, tel. +31 548 61 51 65, www.eurol.com

This document is intended to inform you about product properties and possible applications of Eurol products. Because of continuous product research and development, the information in this document can be changed at all times, without foregoing notice. The analytical data in this product data sheet are typical values. Small deviations, which may occur during the normal manufacturing process of the product, will not affect the quality of the product. Although this information sheet is compiled with great care, Eurol accepts no liability for damage resulting from incompleteness and/or inaccuracies in the text. We recommend that you always follow the manufacturer's instructions.